

Accel-a-Writer® 4N Specifications

Print Speed	20 pages-per-minute (letter)
Resolutions	600 x 600 dpi (standard); 1200 x 1200 dpi (optional)
Processor	IDT 79RC32355
Memory	Standard 64 MB SODIMM, expandable to 256 MB. Optional 63.5mm (2.5") internal IDE drive available.
Toner Cartridge Life	Single Unit 14,000 sheets, (Letter/A4; 5% coverage)
Media Handling	Letter; A3; A4; legal; ledger*; Executive; 330 mm x 469 mm* (324 mm x 468 mm print area); 13" x 18.5"* (12.69" x 18.42" print area); B4; B5; COM 10; Monarch; DL; C5;
Special Stocks	Approved label stock and transparencies
Media Weights	60 to 105 g/m2 (16 to 28 lbs) cassette tray 60 to 135 g/m2 (16 to 36 lbs) multipurpose feeder
Standard Input	500-sheet cassette and a 150-sheet multipurpose feeder
Optional Input	Optional paper feeder and 500-sheet cassette. Optional envelope cassette (capacity of 75)
Standard Output	500 sheets maximum, face down
Duplexing	Optional; Letter/A4; A3/279 mm x 431 mm
Dimensions	(W) 580 mm (22.8") (D) 602 mm (23.68") (H) 413 mm (16.24")
Weight	33.2 kg (73.3 lbs)
Power Requirements	220-240 ~ 50/60 Hz, 2.3 A
Noise Level	Printing - less than 49.5 dB; Standby - less than 35 dB
Printer Languages	Adobe PostScript 3
Typefaces	136 resident PostScript Typefaces; TrueType 42 font rasterizer; Types 1, 3, 4, 5, and 6 PostScript download font support
Standard Interfaces	Simultaneously active – Parallel, USB, 10/100BaseT Ethernet® (EtherTalk®, LPR, IPP, and TCP/IP)

FEATURES

Adobe PostScript 3 - True Adobe PostScript 3 offers reliability, increased performance, and the assurance of compatibility to work from virtually any software application and hardware environment today.

Oversized Printing Format - Custom size output to 330 mm x 469 mm gives you the freedom to print full-bleed with room for trim, registration marks, and more.

High Resolution - Print 600 x 600 dpi for near type-set quality text, line art, and for crisp grayscales or upgrade to 1200 x 1200 dpi for critical jobs that demand the highest quality output.

High Speed Controller - The IDT 79RC32355 processor coupled with XANTÉ's technology enables complex files to print incredibly fast.

Mirror Print - Allows you to print a job from any application so that the image is reversed from left to right providing right-reading, emulsion side down output.

Negative Print - Provides the ability to print a negative image from any application regardless of job make-up.

Duplexing - The Accel-a-Writer 4N's optional duplexing feature allows you to print on both sides of the page automatically. This can be used with page sizes up to A3/279 mm x 431 mm.

Simultaneous Interfacing - The Accel-a-Writer 4N also comes with Parallel, USB, and 10/100BaseT interfaces allow you to print from Macintosh, PC/compatibles, and workstations at the same time. It also supports Ethernet® (EtherTalk®, LPR, IPP, and TCP/IP).

Call XANTÉ Europe today for more information
+31-26-3193210 • Fax +31-26-3193211
 europesales@xante.com • europesupplies@xante.com
www.xante.com

All specs subject to change without notice.

Rev. 8/02

*At 1200 dpi, additional RAM is required to print 279 mm x 431 mm/A3 and larger pages.



Accel-a-Writer[®] 4N

Printing Solutions for Business

XANTÉ[®]'s Accel-a-Writer[®] 4N, designed for general office and small workgroup settings provides an ideal solution for fast, quality printing in any business or CAD environment.

FEATURES

- **Negative Print Capability** regardless of job
- **Network Ready with Ethernet**
- **Up to 1200 x 1200 dpi**
- **Oversized printing up to 13" x 18.5"**
- **Duplexing (optional)**
- **Mirror Print Capabilities**